

| | | |
|--------------------------|---|-----------|
| 泵的技术语 | Pump technology terms | 8 |
| 流量 | Flow rate [$m \approx h$] | 8 |
| 总压头 | Total head [m] | 8 |
| 功耗 | Power consumption | 8 |
| 动态粘度 | Dynamic viscosity η | 9 |
| 流体流动性 | Flow behavior of fluids | 10 |
| 流动类型 | Types of flow | 12 |
| 层流 | Laminar flow | 12 |
| 湍流 | Turbulent flow | 12 |
| R e y n o l d s 值 | Reynolds number | 13 |
| 净绝对进口压头 | NPSH value [m] | 14 |
| 泵净绝对进口压头 | NPSH value of the pump | 14 |
| 设备净绝对进口压头 | NPSH value of the plant | 14 |
| 压力损失计算 | Loss of head calculation | 16 |
| 直管内压力损失趋向 | Loss of head in straight pipe runs | 16 |
| 弯头导致的压力损失 | Loss of head caused by fittings | 17 |
| 泵的选型 | Pump type selection | 19 |
| 离心泵 | Pump type selection | 19 |
| 离心泵的特征 | Centrifugal pumps | 20 |
| Q / H 曲线 | Features of the centrifugal pump | 20 |
| 节流 | Q/H curve | 20 |
| 锐孔板的计算 | Throttling the flow | 21 |
| 叶轮直径计算 | Orifice plate calculation | 21 |
| 泵的转速推測 | Correction of the impeller diameter | 22 |
| 泵的并联 | Pump speed control | 23 |
| 泵的串联 | Parallelly connected pumps | 23 |
| 气蚀 | Pumps connected in series | 24 |
| 蒸气压 | Cavitation | 24 |
| 离心泵型号 | Vapour pressure | 25 |
| 选择标准 | Centrifugal pump types | 26 |
| 离心泵 F P | Selection criteria | 27 |
| 规格选择 | Centrifugal pump FP | 28 |
| F P 性能图表 | Size selection | 28 |
| 泵的功耗 | Centrifugal pump FP performance diagram | 29 |
| 泵的效率 | Power consumption of the pump | 30 |
| 检查 N P S H 值 | Pump efficiency | 30 |
| 自吸离心泵 F Z | Check NPSH value | 31 |
| 规格选择 | Self-priming centrifugal pump FZ | 32 |
| 泵的功耗 | Size selection | 32 |
| 多级离心泵 F M | Power consumption of the pump | 33 |
| | Multistage centrifugal pump FM | 34 |

| | | |
|--|-----------|----------------------------------|
| Positive displacement pumps | 35 | 正位移泵 |
| Features and operating principle of a positive displacement pump | 35 | 正位移泵的工作原理与特征 |
| Operating scheme | 35 | 原理图解 |
| Performance curve | 36 | 性能曲线 |
| Pump speed | 36 | 泵的转速 |
| Viscosity | 36 | 粘度 |
| Clearance losses | 36 | 间隙损失 |
| Designs | 37 | 设计 |
| Design versions | 37 | 设计版本 |
| Selection of design | 38 | 选型 |
| Circumferential piston pump FK, FKL | 38 | 圆周转子泵 F K / F K L |
| Type selection | 39 | 选规格 |
| Case 1: $\eta \leq 1 \text{ mPa s}$ | 40 | 例 1 : $= 1 \text{ mPa s}$ |
| Case 2: viscous product η up to 200 mPa s | 43 | 例 2 $> 200 \text{ mPa s}$ |
| Case 3: viscous product $\eta = 200\text{--}100,000 \text{ mPa s}$ | 47 | 例 3 在 200 - 1000 mPa s 间 |
| Rotary lobe pump FL | 50 | 凸轮转子泵 |
| Selection | 50 | 选规格 |
| Case 1: viscosity $\eta \leq 1 \text{ mPa s}$ | 51 | 例 1 $= 1 \text{ mPa s}$ |
| Case 2: viscous product η up to 500 mPa s | 54 | 例 2 $< 500 \text{ mPa s}$ |
| Case 3: viscous product $\eta = 500\text{--}100,000 \text{ mPa s}$ | 58 | 例 3 $500 < < 1000 \text{ mPa s}$ |
| Mechanical seal selection | 61 | 机械密封选择 |
| Mechanical seal | 61 | 机械密封 |
| Single mechanical seals | 61 | 单面机械密封 |
| Double mechanical seals | 62 | 双面机械密封 |
| “Back to Back” arrangement | 63 | 背对背排列 |
| “Face to Face” arrangement | 64 | 面对面排列 |
| Mechanical seal designs | 65 | 机械密封设计 |
| Seal face materials | 65 | 密封面材料 |
| Elastomers | 66 | 弹性体 |
| Pump cleaning | 67 | 泵的清洗 |
| Cleaning | 67 | 清洗 |
| CIP | 67 | C I P |
| CIP plant cleaning | 67 | C I P 设备清洗 |
| CIP compatible design | 67 | C I P 兼容设计 |
| SIP | 68 | S I P |
| Units of measure and conversion | 69 | 计量单位及转换 |
| Units of measure | 69 | 计量单位 |
| Conversion | 69 | 转换 |